


Crystal Oscillator

FAIRPLY ENTERPRISES INC.

K.C.C Crystal Oscillator (SO-75 Series)




Features & Applications

- 7.0x5.0x1.4mm Size
- Ceramic Package
- CMOS Output
- Low Power Consumption
- RoHS Compliant.

General Specifications

Parameter	SO-75 Series			
	SO-751	SO-753	SO-755	
Input Voltage	1.8V ± 5%	3.3V ± 10%	5.0V ± 10%	
Frequency Range	0.5 ~156.0 MHz	0.5~156.0 MHz	0.5 ~100.0 MHz	
Frequency Stability	A:±25, B: ±50, C: ±30, D: ±20 ppm			
Operating Temperature Range	-10 to +70°C ; -40 to +85°C			
Storage Temperature Range	-55 to +125°C			
Input Current	0.5~9.99MHz	5	7	10
	10~19.99MHz	6	7	15
	20~31.99MHz	6	12	25
	32~49.99MHz	15	20	35
	50~79.99MHz	15	25	50
	80~99.99MHz	20	30	60
	100~156.0MHz	25	40	80
Output Logic High " 1 "	90% VDD			
Output Logic Low " 0 "	10% VDD			
Output Symmetry	40% to 60% (at 50%VDD)			
Rise and Fall Time	0.5~31.99MHz	5	10	10
	32~49.99MHz	5	10	6
	50~79.99MHz	4	8	5
	80~99.99MHz	3	5	5
	100~156.0MHz	3	4	4
Output Load	15pF typical			
Start-Up Time	10ms (Max)			
Aging Rate	±5ppm / Year Max.			

Outline and Dimensions [Unit: mm]



Enable/Disable Function

E/D (#1)	Output (#3)
HIGH (Open)	Operating
LOW	High impedance

Order Part No.:

Product name: **Q 25.000M 75 3 A - G T Z**

① ② ③④⑤ ⑥⑦⑧

- ① KCC Oscillator
- ② Frequency
- ③ Size Type : SO-75=7.2x5.2x1.4mm
- ④ Input Voltage : 3=3.3V
- ⑤ Frequency Stability : A=±25ppm
- ⑥ RoHS Compliant
- ⑦ Operating temperature : T= -40°C to +85°C
- ⑧ Internal identification code

FAIRPLY
ENTERPRISES INC.

飛谷企業有限公司 FAIRPLY ENTERPRISES INC.

地址 : 10058 台北市中正區八德路一段 5 號 5 樓之一 B 室

ADD : Rm. B, 5F.-1, No.5, Sec. 1, Bade Rd., Zhongzheng Dist., Taipei City 100, Taiwan (R.O.C.)

TEL: (02)-2321-5496

FAX: (02)-2321-7675

E-MAIL : juan66@ms27.hinet.net

fei@ms2.hinet.net

<http://www.fairply.com/>